



Audio

Frequency response 55Hz - 22kHz
Drivers Custom 20mm silk dome tweeters,
 75mm polypropylene cone neodymium woofers
Amplifier 20W Class AB
Cabinet type Tuned bass reflex
Digital to analogue Cirrus 24-bit stereo DAC

Connectivity

Bluetooth V4.0, A2DP, aptX, SBC, AAC
Aux input 3.5mm stereo jack (2.5Vrms max)
Digital input 24-bit 192-kHz optical TOSLINK
Subwoofer output RCA phono (700mVrms)

Features

Auto-mono Use as a single speaker
Snooze mode Auto-standby and wake-up
BackPack battery pack Optional
Adjustable input levels Aux, optical
Wall mounting 1 x 1/4-20 UNC threaded insert

General Specifications

Finishes Rich walnut veneer or soft grey lacquer with grey woven fabric grille
Box contains Left speaker, right speaker, AC power adapter, braided speaker interconnect cable, remote control, remote control battery (CR2025), user guide
Power adapter 100-240VAC 50-60Hz input
 14VDC 2A output, 1.8m cable, 2.1 x 5.5mm DC plug
Power consumption 0.5W standby, 9W typical
Product dimensions W130 x H175 x D140mm
Product weight Right 1.3kg, Left 1.1kg
Inner carton dimensions W385 x H285 x D235mm
Packaged weight 3.6kg (pair)
Shipping carton dimensions W490 x H320 x D410mm
Shipping carton weight 0.7kg
Gross weight 7.9kg (box of 2 pairs)
Rich Walnut product code/EAN
 MR1B-WAL / 090660102510
Soft Grey product code/EAN
 MR1B-SG / 090660102527